

## Environmental Protection Agency

§ 98.72

Parameter	Data source
CO <sub>2</sub> Emissions From Pitch Volatiles Combustion (CWPB and SWPB)	
MP: metal production (metric tons Al) .....	Individual facility records.
PC: annual paste consumption (metric ton/metric ton Al) .....	Individual facility records.
CSM: annual emissions of cyclohexane soluble matter (kg/metric ton Al) .....	HSS: 4.0. VSS: 0.5.
BC: binder content of paste (percent weight) .....	Dry Paste: 24. Wet Paste: 27.
S <sub>p</sub> : sulfur content of pitch (percent weight) .....	0.6.
Ash <sub>p</sub> : ash content of pitch (percent weight) .....	0.2.
H <sub>p</sub> : hydrogen content of pitch (percent weight) .....	3.3.
S <sub>c</sub> : sulfur content in calcined coke (percent weight) .....	1.9.
Ash <sub>c</sub> : ash content in calcined coke (percent weight) .....	0.2.
CD: carbon in skimmed dust from Søderberg cells (metric ton C/metric ton Al) .....	0.01.
CO <sub>2</sub> Emissions from Pitch Volatiles Combustion (VSS and HSS)	
GA: initial weight of green anodes (metric tons) .....	Individual facility records.
H <sub>a</sub> : annual hydrogen content in green anodes (metric tons) .....	0.005 × GA.
BA: annual baked anode production (metric tons) .....	Individual facility records.
WT: annual waste tar collected (metric tons) .....	(a) 0.005 × GA.
(a) Riedhammer furnaces .....	(b) insignificant.
(b) all other furnaces .....	
CO <sub>2</sub> Emissions From Bake Furnace Packing Materials (CWPB and SWPB)	
PCC: annual packing coke consumption (metric tons/metric ton baked anode) .....	0.015.
BA: annual baked anode production (metric tons) .....	Individual facility records.
S <sub>pc</sub> : sulfur content in packing coke (percent weight) .....	2.
Ash <sub>pc</sub> : ash content in packing coke (percent weight) .....	2.5.

[74 FR 56374, Oct. 30, 2009, as amended at 75 FR 79156, Dec. 17, 2010]

## Subpart G—Ammonia Manufacturing

### § 98.70 Definition of source category.

The ammonia manufacturing source category comprises the process units listed in paragraphs (a) and (b) of this section.

(a) Ammonia manufacturing processes in which ammonia is manufactured from a fossil-based feedstock produced via steam reforming of a hydrocarbon.

(b) Ammonia manufacturing processes in which ammonia is manufactured through the gasification of solid and liquid raw material.

### § 98.71 Reporting threshold.

You must report GHG emissions under this subpart if your facility contains an ammonia manufacturing process and the facility meets the requirements of either § 98.2(a)(1) or (2).

### § 98.72 GHGs to report.

You must report:

(a) CO<sub>2</sub> process emissions from steam reforming of a hydrocarbon or the gasification of solid and liquid raw material, reported for each ammonia manufacturing process unit following the requirements of this subpart (CO<sub>2</sub> process emissions reported under this subpart may include CO<sub>2</sub> that is later consumed on site for urea production, and therefore is not released to the ambient air from the ammonia manufacturing process unit).

(b) CO<sub>2</sub>, CH<sub>4</sub>, and N<sub>2</sub>O emissions from each stationary fuel combustion unit. You must report these emissions under subpart C of this part (General Stationary Fuel Combustion Sources), by following the requirements of subpart C, except that for ammonia manufacturing processes subpart C does not apply to any CO<sub>2</sub> resulting from combustion of the waste recycle stream (commonly referred to as the purge gas stream).

(c) CO<sub>2</sub> emissions collected and transferred off site under subpart PP of this part (Suppliers of CO<sub>2</sub>), following the requirements of subpart PP.

[74 FR 56374, Oct. 30, 2009, as amended at 75 FR 79156, Dec. 17, 2010]